



2026 Sporting Regulations
Season XXI
 Ver 21.0 (11-25-25)

A. DEFINITIONS

Event Definitions

a.1. The AZGT Championship is a closed wheel stock class series.

Eligible Cars

a.2. Any 1:28-1:24 scale car, subject to Technical Regulations (Sec E).

B. PRE-RACE (all formats)

Scrutineering

b.1. Cars must be provided to the inspector for Scrutineering prior to the race.

C. SPRINT RACE

Sprint Grid

c.1. Cars grid in order of points or randomly if no points are yet scored.

Sprint Race

c.2. Races are run in two Sprints: A 5 minute "A Sprint" followed by a 10 minute "B Sprint".

c.3. Grid positions for the 'A' Sprint are by points. Grid positions for the 'B' Sprint are the 'A' Sprint finish order.

D. SCORING

d.1.	5min		10min	
	Fin	Pts	Fin	Pts
	1 st	8	1 st	16
	2 nd	7	2 nd	13
	3 rd	6	3 rd	11
	4 th	5	4 th	9
	5 th	4	5 th	7
	6 th	3	6 th	5
	7 th	2	7 th	3
	8 th +	1	8 th +	1

d.2. If multiple Heats are run, determine points as though all cars ran together based on lap data.

d.3 Bonus Points

Bonus Points are awarded to the driver setting the fastest lap of each race, and to each driver that lead a lap in a race.

Fastest lap = 1 points

Lead a lap = 1 points

d.4. Fastest lap tie awards the bonus to all drivers recording that time.

d.5. If multiple Heats are run, determine points as though all cars ran together based on lap data. "Lead a Lap" bonus is only scored from the leader Heat. Only one "Fastest Lap" bonus is scored regardless of which Heat it was set in.

E. TECHNICAL REGULATIONS

Chassis

e.1. Kyosho Mini-Z or equivalent other manufacturer chassis. The core structure must be primarily plastic like stock Kyosho. Parts such as suspension/rear pod may be metal / carbon fiber.

e.2. RWD, FWD and AWD are legal. AWD may be altered to run as FWD or RWD.

e.3. Wheelbase shall be 106mm or less.

e.4. Trimming of chassis material is permitted.

Electronics

e.5. Any control board. No driver aids (ie gyro)

Motor

e.6. Any 70t or greater (ie 80t) 130 class brush, or 3500kv or less brushless motor.

Batteries

e.7. Any NiMh, NiCd or Alkaline AAA size batteries in a four cell arrangement.

Body

e.8. 1:28-1:24 scale plastic forming a complete shell around the chassis and fenders over wheels.

e.9. Trimming of material is permitted. Windows must be installed on closed cockpit vehicles, but may use Lexan window/roof replacements. Ablative parts such as mirrors or light covers may be omitted.

e.10. Anti-rail-snagging bumpers may be added but must be fixed. No moving parts.

Tires

e.11. Any rubber tire. Front/rear traction patches may be no wider than 8.5mm front/11mm rear.

e.12. No traction compounds. Tire warmers are allowed.

Weight

e.13.
Complete car min 160g race-ready with batteries.
Body only minimum 24g.